

DRYLOK® Etch Masonry Cleaner

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • **FAX:** 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

DRYLOK Etch cleans and etches concrete, stone, tile and brick. DRYLOK Etch removes efflorescence (salt-like deposits) and excess mortar. It's perfect for etching concrete and galvanized surfaces prior to painting. Safer to use than muriatic acid.

- Prepares smooth concrete for painting
- Removes efflorescence
- Cleans mortar from brick and tile
- Conditions galvanized surfaces for painting
- No harmful fumes, safer and easier than muriatic acid
- Can be used indoors

BASIC USES

Clean and etch interior and exterior concrete, stone, tile galvanized metal and brick.

LIMITATIONS

Do not use galvanized container. Kills plants and shrubbery.

TECHNICAL DATA

COMPOSITION:

Sulfamic acid

SHEEN:

N/A

% WEIGHT SOLIDS:

100%

% VOLUME SOLIDS:

100%

DENSITY (LBS./US GAL.):

17.74 ± 0.3

VISCOSITY:

N/A

pH:

1.18 (1% solution/water)

COLORS:

N/A

ACTIVE TIME:

• N/A

CLEAN UP:

Water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US GAL.):

• 300 sq. ft./12 oz. when mixed with 1 gallon of water.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

N/A

FREEZE/THAW:

N/A

CONTAINER SIZES:

Twelve ounce (US) containers

VOC

N/A

TINTING

N/A

SURFACE PREPARATION

Wear eye protection and chemical resistant gloves. Remove dirt, dust, grease and oil by washing with a detergent solution or UGL DRYLOK Concrete Cleaner & Degreaser. Allow the surface to dry before applying DRYLOK Etch.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

MIXING

To remove efflorescence, clean mortar or etch galvanized surfaces, dissolve 12 ounces of Etch in one gallon of warm water; to etch concrete prior to painting, use 12 ounces of Etch to one-half gallon of warm water. Do not use galvanized container. Wear rubber gloves and eye protection.

APPLICATION

Apply with a stiff brush. Wait 20-30 minutes. Flush thoroughly with clean water.

Treat smooth concrete with DRYLOK Etch. A properly etched surface should look and feel slightly rough, like fine sandpaper. If surface remains smooth, repeat the etching procedure until the surface has the proper texture. Thoroughly rinse the surface with clean water.

NOTE: Allow etching solution to remain on the surface for at least 20 minutes. While etching, the concrete surface should bubble. If some areas do not, this indicates deep oil



ACTIVE TIME:
20-30 Minutes



CLEAN-UP:
Water



COVERAGE:
1 Application



SPREAD RATE:
300 Sq. Ft./12 Oz.
when mixed with
1 Gallon of water

or grease stains requiring additional cleaning. Scrub these areas again with a heavy duty detergent or UGL DRYLOK Concrete Cleaner & Degreaser and repeat the etching procedure. Allow the surface to dry at least 24 hours before staining or painting.

CAUTION

TOXIC-IRRITANT. Contains sulfamic acid. May cause burns. Irritates nose, throat and skin. Avoid contact with skin, eyes and clothing. In case of contact, flush with water for at least 15 minutes; for eyes, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician. If inhaled, remove to fresh air. If difficulty in breathing persists, call a physician. If swallowed, give 1 or 2 glasses of water. Call physician immediately. These precautions apply to both dry form and solution.

Kills plants and shrubbery.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID

EYES: Immediately flush with plenty of water for at least 15 minutes. Consult a physician.

SKIN: Flush skin with water. Consult a physician if irritation is present.

INGESTION: Drink a lot of water. Contact a physician.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

WARRANTY

N/A

SPECIFICATION

N/A



Etch
12 OZ. 6/Case01908

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.